

# INFRARED FOREHEAD CLINICAL THERMOMETER

Providing **Safety** to **Every Industry, Every Scenario.**

Customer Service 800.577.3171  
salesny@allfasteners.com




## Now Stocking Non-Contact Infrared Forehead Thermometers.

**IN STOCK**

Clinical Forehead Infrared Thermometers ensure accurate and stable body temperature readings. From a distance of around 2in, all you have to do is point it towards the forehead to read the temperature shown on the LCD screen.

The Non-Contact Forehead IR Thermometer is specially designed to take the body temperature of a person regardless of room temperature.

Part No.	Description		\$ / EACH
13IRFT10	Infrared Forehead Clinical Thermometer	1	<b>\$69.00</b>

## SPECIFICATIONS ▾

**Non-Contact**

**1 Second Response Time**

**2in Measuring Distance**

**RANGE BODY MODE** 89°F TO 109°F

**OPERATION ENVIRONMENT** TEM. 50°F TO 104°F HUMIDITY 30% RH 85%RH

**FUNCTIONS** 30 MEMORIES, BEEPER FUNCTION, FEVER ALARM >99.50°F

**BASIC ACCURACY** ±0.10C 96.8 TO 102°C

**MEASURING DISTANCE** 2IN

**RESPONSE TIME** 1 SECOND

**STORAGE ENVIRONMENT** TEM. 40F +1400F HUMIDITY 10%RH 95%RH

**POWER SUPPLY** DC 3V

# INFRARED NON-CONTACT THERMOMETER

Providing **Safety** to **Every Industry, Every Scenario.**

Customer Service 800.577.3171  
salesny@allfasteners.com



## Now Stocking Non-Contact Infrared Thermometers.

**IN STOCK**

- Battery Operated
- Non-Contact
- Certificates: FDA Approved, CE Certified, ISO 13485
- Multiple Uses as shown to the right
- Color Coding Backlights for Easy Diagnosis



Part No.	Description	Quantity	\$ / EACH
13NCFT	Infrared Thermometer	1	\$95.00

- Ask about quantity discounts

Taking Kid's Temperatures



Taking Elderly Temperatures



Testing Bottle Temperatures



Testing Food Temperatures



## SPECIFICATIONS

POWER SUPPLY	2x AAA Batteries
EFFECTIVE DISTANCE	2" - 3.15" (5cm - 8cm)
RANGE	Body Temp: 77°F - 109.22°F (25°C - 42.9°C) Object Temp: 32°F - 199.4°F (0°C - 93°C)
WORKING CONDITION	60.8°F - 104°F (16°C - 40°C), Relative Humidity ≤ 85%
STORAGE CONDITION	-4°F - 131°F (-20°C - 55°C), Relative Humidity ≤ 85%
RESOLUTION	32.18°F (0.1°C)
REPETITIVENESS	≤ ±32.36°F (≤ ±0.2°C)
POWER CONSUMPTION	When off ≤ 10uW; When Measuring ≤ 30mW
TESTING TIME	<0.5s
WEIGHT	About 3.4 oz. (97g)
SIZE	3.7" x 6" x 1.6" (93 x 153 x 41 mm)
GRADE OF WATERPROOF	IP22
MODE OF OPERATION	Continuous Operation
PRODUCT LIFE	5 Years

